

FDA
EC

PU60A SOFT blue smooth

M BELT
DOPRAVNÍ SYSTÉMY

Order No.	Diameter \varnothing		Cross section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley \varnothing		Fmax/belt (Standard)*	
	mm	inch			m	ft	mm	inch	kg	lbs
FBRF030LGS	3,0	1/8	0,071	0,9	200	656	10	0,4	0,9	2,0
FBRF040LGS	4,0	5/32	0,126	1,6	200	656	20	0,8	1,5	3,3
FBRF050LGS	5,0	1/5	0,181	2,2	100	328	30	1,2	2,2	4,9
FBRF060LGS	6,0	7/32	0,283	3,4	100	328	40	1,6	3,4	7,5
FBRF080LGS	8,0	5/16	0,500	6,0	100	328	50	1,9	6,0	13,2
FBRF095LGS	9,5	3/8	0,710	8,5	100	328	65	2,6	8,5	18,7
FBRF100LGS	10,0	7/16	0,785	9,4	100	328	70	2,7	9,4	20,7

approx. 65° Shore A

Recommended pretension

5...10 %

Coefficient of friction μ : Steel: approx. 0,90 | PE: approx. 0,55 | HDPE: approx. 0,50 | **FDA/EC compliant****

* = coefficient of friction μ :0,5