

FDA  
EC  
USDA

## Polyester TPE63D beige smooth, reinforced polyester

**M BELT**  
DOPRAVNÍ SYSTÉMY

Order No.	Diameter ∅		Cross section cm <sup>2</sup>	approx. weight kg/100 m	Standard Roll		Recommended Min. pulley∅		Fmax/belt (Standard)*		Fmax/belt (overlap)	
	mm	inch			ft	(m)	mm	inch	kg	lbs	kg	lbs
FBRT095NGA	9,5	3/8	0,710	8,5	500	152,4	150	5,9	59,4	130,6	190	418
FBRT100NGA	10,0	7/16	0,785	9,4	500	152,4	150	5,9	67,0	147,4	190	418
FBRT120NGA	12,0	15/32	1,130	13,5	500	152,4	190	7,5	96,0	211,2	190	418
FBRT125NGA	12,5	1/2	1,230	14,8	500	152,4	200	7,8	102,8	226,2	190	418

63° Shore D · approx. >100° Shore A

Recommended pretension

0,5...2 %

Coefficient of friction  $\mu$ : Steel: approx. 0,30 | PE: approx. 0,15 | HDPE: approx. 0,10 | **FDA/EC/USDA compliant**

\* = coefficient of friction  $\mu$ :0,5; \*\* Overlap +30%