

PU85A green rough hollow round belt



M BELT
DOPRAVNÍ SYSTÉMY

approx. 88° Shore A

Recommended pretension:
welded 4...8 %
Fitting connector max. 3...6 %

Order No.	Diameter \varnothing		Cross section cm ²	approx. weight kg/100 m	Standard Roll		Recommended Min. pulley \varnothing		Fmax/belt (Standard)*	
	Outside	Inside			m	ft	mm	inch	kg	lbs
FBHP85A048R	4,8	1,8	0,147	1,8	200	656	35	1,4	5,3	11,7
FBHP85A063R	6,3	2,5	0,261	3,2	100	328	55	2,2	9,4	20,6
FBHP85A080R	8,0	3,2	0,420	5,1	100	328	65	2,6	15,3	33,7
FBHP85A095R	9,5	3,8	0,600	7,2	100	328	75	3,0	20,4	44,9
FBHP85A125R	12,5	5,2	1,020	12,4	50	164	100	3,9	36,7	80,8
FBHP85A150R	15,0	5,2	1,560	19,0	50	164	120	4,7	57,1	125,7

Coefficient of friction μ : Steel: approx. 0,45 | PE: approx. 0,35 | HDPE: approx. 0,30

* = coefficient of friction μ :0,5