

# PU90A white smooth hollow round belts



Order No.	Diameter $\varnothing$		Cross section cm <sup>2</sup>	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley $\varnothing$		Fmax/belt (Standard)*	
	Outside	Inside			m	ft	mm	inch	kg	lbs
FBHP90A048	4,8	1,8	0,147	1,8	200	656	45	1,8	8,6	19,0
FBHP90A063	6,3	2,5	0,261	3,2	100	328	60	2,4	12,4	27,2
FBHP90A080	8,0	3,2	0,420	5,1	100	328	75	3,0	19,0	41,8
FBHP90A095	9,5	3,8	0,600	7,2	100	328	85	3,4	28,5	62,7
FBHP90A125	12,5	5,2	1,020	12,4	50	164	115	4,5	47,5	104,5
FBHP90A150	15,0	5,2	1,560	19,0	50	164	140	5,5	72,3	159,0

**M BELT**  
DOPRAVNÍ SYSTÉMY

approx. 92° Shore A

Recommended pretension:

welded 3...5 %

Fitting connector max. 2...4 %

Coefficient of friction  $\mu$ : Steel: approx. 0,50 | PE: approx. 0,30 | HDPE: approx. 0,25

\* = coefficient of friction  $\mu$ :0,5